



TECHNOLOGICALLY
ADVANCED ENERGY PRODUCTS

Product Preview & Price List 2018

Price effective: May, 2018





TABLE OF CONTENT

Company Overview	01
Industrial Plugs & Sockets	02
Variabox	05
Eco Box Enclosure & Junction Boxes	06
LV Switchboards	08
Metering System	11
Energy Management System	14
Power Capacitors	19
Automatic Power Factor Controller	21
Harmonic Block Reactors / Thyristor Switching Module	23
PF Compensator	24
Activcomp & Harmonic Filtration System	25
Active Harmonic Filter	26

Company



Energy efficiency is one of the rising needs in the urbanized world and many products are introduced to fulfill this demand.

One of the crucial advantages that energy efficiency products bring is the reduction of cost. For implementing cost saving measures, industries are looking forward to products that will also help them in maintaining their position in the growing market.

A leader in the Energy Saving and Power Quality Management sector of India, Neptune India set its foot in the market with a dedicated approach and a strong vision to become a specialist in the field of energy saving. Today, the company strives forth with its love for energy and has taken huge steps to implement best solutions in all aspects of energy.

Established in the year 1989, Neptune India; with over 30,000 plus installations across the country and having a pan-India sales & support network. Neptune is a known brand in the Power Factor Correction, Energy Management, Harmonic Filtration & Power Distribution Products.

INDUSTRIAL PLUG & SOCKETS HSN-8536

SURFACE MOUNTING



Surface Mounting Socket



Surface Mounting Socket

Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SPLASH PROOF IP-44						
16/20	111	720	11645	810	100	810
32	11651	900	11646	980	101	980
63	1104	3,595	1127	3,490	1124	3,490
WATER TIGHT IP-67						
16/20	1133	1,190	1137	1,540	1143	1,540
32	1145	1,490	1149	1,860	1155	1,860
63	1157	4,590	1161	4,490	1112	4,490
125	11427	15,000	11441	15,820	11447	15,820

PANEL MOUNTING



Panel Mounting Socket



Panel Mounting Socket



Panel Mounting Socket



Panel Mounting Socket

Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SOCKET-OUTLET ANGLED SPLASH PROOF IP-44						
16/20	1217	440	1221	720	12078	720
32	12310	740	1233	890	1215	890
63	12135	3,095	-	3,170	12380	3,160
SOCKET-OUTLET STRAIGHT SPLASH PROOF IP-44						
16/20	131	440	1324	710	132001	710
32	13007	740	13011	900	1333	900
63	1307	3,095	134	3,160	136	3,160
SOCKET-OUTLET ANGLED WATER TIGHT IP-67						
16/20	1266	930	1270	1,020	1276	1,020
32	1278	1,160	1282	1,310	1288	1,310
63	12001	3,690	1200	3,470	129	3,470
125	12100	12,100	12104	12,400	12108	12,400
SOCKET-OUTLET STRAIGHT WATER TIGHT IP-67						
16/20	1372	930	1376	1,020	1382	1,020
32	13024	1,160	13028	1,310	1370	1,310
63	1396	3,690	13100	3,470	13104	3,470
125	13452	12,100	13447	12,400	13451	12,400

INDUSTRIAL PLUG & SOCKETS

HSN-8536

PANEL MOUNTING



Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SPLASH PROOF IP-44						
16/20	71094	440	-	-	-	-
16/20	7370	390	-	-	-	-
16/20	231	560	-	-	-	-

PLUG



Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SPLASH PROOF IP-44						
16/20	21001	370	21005	520	203	520
32	21013	620	21017	730	204	730
63	2104	3,190	2151	2,890	21590	2,890
WATER TIGHT IP-67						
16/20	210576	840	21349	1,110	21239	1,110
32	210594	1,260	21351	1,340	210607	1,340
63	2181	3,690	2185	3,360	2189	3,360
125	2191	10,870	2195	10,700	2199	10,700
SPLASH PROOF IP-44						
16/20	31001	560	31005	680	303	680
32	31013	730	31017	930	304	930
63	3104	3,750	3151	3,790	3112	3,790
WATER TIGHT IP-67						
16/20	310333	1,220	31241	1,490	31243	1,490
32	31244	1,720	31245	1,890	310364	1,890
63	3181	4,050	3185	3,850	3124	3,850
125	3191	12,500	3195	12,740	3199	12,740

INDUSTRIAL PLUG & SOCKETS HSN-8536

SURFACE MOUNTING



Socket-outlet with MCB Provision



Socket-outlet interlocked

Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SPLASH PROOF IP-44						
16/20	15019	4,690	-	5,200	15059	5,200
32	15030	5,310	-	6,130	1585	6,130
63	-	-	-	12,700	15036	12,700
WATER TIGHT IP-67						
16/20	15024	4,790	15098	5,400	15028	5,400
32	15352	5,410	15111	6,400	15112	6,400
63	-	-	15000	12,920	15001	12,920
125	-	-	15158	38,700	15160	38,700
SPLASH PROOF IP-44						
16/20	1619	6,200	1610	8,900	1611	8,900
32	16097	8,200	16596	9,990	16043	9,990
63	-	-	16605	18,990	16603	18,990
WATER TIGHT IP-67						
16/20	1600	6,200	1602	8,990	1604	8,990
32	16104	8,770	160178	10,930	160177	10,930
63	-	-	16604	20,400	16602	20,400
125	-	-	16621	66,100	16622	66,100

DOMESTIC AC/ INDUSTRIAL OUTLET

Plug/Socket combined in metal enclosure



Plug/Socket combined in Polycarbonate enclosure



Appliance Inlet



Ampere	2P+ \perp 230V		3P+ \perp 415V		3P+N+ \perp 230/415V	
	Part No.	L.P. ₹	Part No.	L.P. ₹	Part No.	L.P. ₹
SPLASH PROOF IP-44						
16/20	1201 SP/DP	1,360/1,370	-	1,940	3201	1,940
32	1202 SP/DP	1,890	-	2,450	3202	2,450
63	1203	7,870	-	7,730	3203	7,730
PLUG SOCKET COMBINED IN POLYCARBONATE						
16/20	901	1,610	-	2,280	903	2,280
32	911	2,180	-	2,700	913	2,700
SPLASH PROOF IP-44						
16/20	261	1,080	-	1,140	2612	1,140
32	2662	1,610	-	2,270	2600	2,270

VARIABOX The new generation of distributors HSN-8537

The new VARIABOX from Bals meets all requirements for a modern distributor housing and can be individually configured in 5 different sizes with versions S, M, L, & XXL as surface mounting or mobile combination. We have the right distributor for every user. Configuration according to individual specifications on the basis of pre-defined, encoded flanges, which offer a maximum level of safety during the initial installation & /or maintenance. With their robust design in a high grade & durable, quality plastic, their good seal, the modular expansion option & many innovative extra features, the new VARIABOX proves itself even under the most adverse conditions.



Features

- ▶ Ready wired for installation
- ▶ Housing made of high-grade, impact-resistant plastic
- ▶ Top and bottom can be sealed together
- ▶ Permanently attached cover screws
- ▶ All CEE socket outlets with screw less, maintenance-free QUICK-CONNECT connection technology
- ▶ Colors, bottom-black, top-electro grey (Housing top optionally available in the colors yellow, red, blue or silver)
- ▶ With high quality handle
- ▶ Coded flange system for maximum safety during initial installation and maintenance
- ▶ Fuse elements arranged below transparent, lockable operating window with user friendly OTC mechanics (one touch close)

Item Code	Dimensions	L.P. ₹
Variabox-Small	130 x 230 mm	8,550/-
Variabox-Medium	260 x 230 mm	10,350/-
Variabox-Large	390 x 230 mm	13,950/-
Variabox-Extra Large	520 x 230 mm	17,550/-
10 Way Window	-	1,620/-
4 Way Window	-	1,575/-

ECO BOX ENCLOSURE & JUNCTION BOXES HSN-8538

Modular Distribution Board – IP 65



Modular Distribution Board



Modular Enclosure



Junction Boxes

Dimensions LxWxH (mm)	Part No.	L.P. ₹
MODULAR DISTRIBUTION BOARDS		
150 x 300 x 215	9150	2,390/-
300 x 300 x 215	9300	3,100/-
450 x 300 x 215	9450	4,690/-
600 x 300 x 215	9600	5,870/-
MODULAR ENCLOSURE		
180 x 180 x 135	6180	1,380/-
180 x 240 x 135	6260	1,620/-
240 x 320 x 135	6320	2,940/-
320 x 420 x 135	6420	4,050/-
420 x 640 x 160	6520	8,910/-
JUNCTION BOXES		
90 x 90 x 50	1001	280/-
100 x 100 x 60	1002	340/-
110 x 140 x 70	1003	590/-
130 x 130 x 100	1004	670/-
130 x 170 x 80	1005	750/-
170 x 210 x 100	1006	1,490/-

DESCRIPTION

Modular Enclosure

- ▶ Impact resistant modular polycarbonate distribution boards
- ▶ Chemical resistant
- ▶ Solid and Stable
- ▶ Self-extinguishing
- ▶ Weather Resistant
- ▶ Corrosion free screws

Eco Box Modular Distribution Boards

- ▶ Impact resistant modular polycarbonate enclosures
- ▶ Chemical resistant
- ▶ Solid and Stable
- ▶ Self-extinguishing
- ▶ Weather Resistant
- ▶ Corrosion free screws
- ▶ Self internal fixing center / fixing center outside
- ▶ Cable entry to client's specifications

Mobile Distribution Rubber Boards HSN-8537



Customized IP 65 L.V. Distribution Panels & Feeder Pillar HSN-8537




Enclosures HSN-8538 IP-65



Part No.	Rating	LxWxH (mm)	L.P. ₹
3004	4 Way	160 x 225 x 100	1,400/-
3008	8 Way	225 x 225 x 100	2,280/-
3304	12 Way	300 x 225 x 100	3,290/-
3308	24 Way	300 x 400 x 100	5,700/-
3312	36 Way	300 x 600x 100	8,400/-

Rubber distribution & IP 65 L.V. Distribution Panel- **Price as per specification on request**

Windows HSN-8538



No. of ways	Part No.	L.P. ₹
2 Way	5882	450/-
4 Way	5891	495/-
8 Way	58010	630/-
12 Way	58019	790/-

LV SWITCHBOARDS



LV SWITCHBOARDS HSN-8537

NEPTUNE Power – D Modular Switchboards

1. Fully bolted Structure, CPRI Type Tested confirming to IS 8623/IEC 61439
2. Available up to 5000A current rating
3. Easily extensible on either side, makes the enclosure future proof
4. Single Front and space saving double front can be constructed
5. Type of construction up to form 4b
6. Standard sizes available off the shelf, thus cutting down lead time & inventory carrying cost
7. Appropriate level for degree of protection (special design available for higher level of protection)
8. Door can be hinged on either side offering greater flexibility to configure as per the site conditions
9. Spacious arrangement for cable termination & appropriate support for cable routing
10. Provision for BMS compatibility



NEPTUNE POWER D SWITCHBOARDS ARE INTELLIGENT - EVERY INCOMING / OUTGOING FEEDER
CAN BE MONITORED & CONTROLLED REMOTELY WITH ENERGY MANAGEMENT SYSTEM.

NEPTUNE Elsteel Techno Modular Switchboards (TTA)

Constructional Features

1. Enclosures are modular in construction and expandable in all three dimension in easily measurable multiples of 200 MM
2. Enclosures provide upto form 4b type separation to ensure absolute operational safety
3. Ingres protection level of the enclosures provided upto IP 54/55
4. Enclosures to provide drill less system for all connections of busbars to maintain high efficiency and minimal losses (Low heat dissipation)
5. All load bearing structures of the moduler enclosures made of electro galvanized steel and powder coated ensuring durability and resistance to corrosion.
6. Moduler structure, Draw out / Semi draw out construction.

Test certifications

1. Enclosures are constructed as fully type tested assemblies (TTA), confirming to IEC 61439-1/2 standards.
2. Type tested for special tests like Seismic Test as per IEC 68-3-3, Vibration test as per IEC 68-2-6 & IEC 68-2-36, Arc containment as per IEC 61641 standards etc.
3. ASB Type approval certificate for shipboard and associated marine and offshore installations.



METERING PRODUCTS RANGE



POWER ANALYSERS HSN-9028

M8 Power Analyzer

L.P. ₹ 5,400/-



- + 7 segment bright LED display, Three rows
- + Site Programmable CT and PT ratio
- + True RMS measurement
- + Password protection
- + Harmonic measurement (THD)
- + Parameters- Phase wise-VL-L, VL-N, Amp, Hz, PF, KW, KVA, KVAR, Total energy, THDV, THDI & run hours
- + M8 plus with above features, available with RS 485 (price on request)

M9 Power Analyzer

L.P. ₹ 8,600/-



- + 7 segment bright LED display, Four rows
- + Site Programmable CT and PT ratio
- + True RMS measurement
- + Password protection
- + Maximum demand with relay contact with RS 485
- + Harmonic measurement (Total & Individual)
- + Parameters- Phase wise-VL-L, VL-N, Amp, Hz, PF, KW, KVA, KVAR, KVAH, KVARH, KWH energy, dual energy, THDV, THDI & run hours, MD & upto 31st Harmonic through RS 485

M20 Power Analyzer

L.P. ₹ 9,900/-



- + LCD display with backlight
- + Site Programmable CT and PT ratio
- + True RMS measurement
- + Password protection
- + Bargraph for percentage current
- + 8 digit energy display
- + Maximum demand with relay contact RS485 computer interface
- + Harmonic measurement (Total & Individual)
- + Universal Auxiliary supply
- + Parameters- Phase wise-VL-L, VL-N, Amp, Hz, PF, KW, KVA, KVAR, KVAH, KVARH, KWH energy, dual energy, THDV, THDI & run hours, MD & upto 31st Harmonic through RS 485

M30 Power Analyzer

L.P. ₹ 32,400/-



- + Measurement up to 31 Harmonic for current & voltage separately
- + Total Harmonic Distortion for Voltage & Current (THD-V/ 1%)
- + RS-485 Communication and 2 nos of Relay contact output
- + Energy Pulse output or Digital input (optional)
- + 4-20mA angle O/P for PLC's/ other auxiliary tracking methods (optional)
- + Display demand value, max/min values & Neutral Current
- + Parameters and demand values are stores even if supply voltage is cut off
- + Data logging (1 Mb internal memory) with real time clock
- + Password protection for setup

DIGITAL METERING HSN-9028

1 Phase Meter (Ammeter/Voltmeter)

LP. ₹ 880/-



- + LED type, 7-segment, 4 Digit display
- + CT / PT ratio site selectable
- + True RMS measurement & Password protection
- + Auto ranging
- + Auxiliary supply 90-270 VAC/DC
- + Auto/manual page scrolling
- + Parameters – A / V, THDI/THDV & Hz

3 Phase Meter (Ammeter/Voltmeter)

LP. ₹ 1,395/-



- + LED type, 7-segment, 4 Digit display
- + CT / PT ratio site selectable
- + True RMS measurement & password protection
- + Auxiliary supply, self powered
- + Auto/Manual page scrolling
- + Auto ranging
- + Parameters- A / V, Amps Phase wise and Avg / VL-L, VL-N, THDI/THDV & Hz

Advance VIF Meter

LP. ₹ 2,100/-



- + LED type, 7-segment, 3 Digit display
- + CT / PT ratio site selectable
- + True RMS measurement & password protection
- + Auto ranging
- + Auxiliary supply, 40-270 V
- + Auto/Manual page scrolling
- + Parameter measured are V, I, Hz, P.F, KW, KVα, RPM

Earth Leakage Relay HSN-8536 with CBCT HSN-8504



- + Latest micro controller based technology with true RMS sensing
- + Single model covers from 30 mA to 30 A-completely programmable in 10 steps
- + Monitors cable connection between ELR/CBCT
- + Bar graph to indicate % of leakage current in the system
- + Alarm available at 50% set of value & tripping at 80-90% of set value
- + Core balance CT (CBCT) available in 4 sizes: 35/70/120/210mm (dia)
- + Delay adjustable from 0-10 sect in 10 steps
- + Also available with LCD Display and Flush Mounting

Item Code	L.P. ₹
Earth leakage Relay with 35 mm CBCT	3,960/-
Earth leakage Relay with 70 mm CBCT	4,320/-
Earth leakage Relay with 120 mm CBCT	4,770/-
Earth leakage Relay with 210 mm CBCT	6,570/-


Special sizes of CBCT also available on request. Display optional available only for Flush Mounting

ENERGY MANAGEMENT SYSTEM

When efficiency is
your target



Energy Management System



Salient features of Neptune EMS are:

- ▶ Historic trend charts
- ▶ On-line trend charts
- ▶ Performance reports
- ▶ Energy reports
- ▶ Cost reports
- ▶ Budget Reports
- ▶ Alarm Reports
- ▶ Specific energy consumption reports
- ▶ Run hour reports

MEASURE to Manage Energy

Neptune EMS uses advance range of fault, energy and power monitoring devices which can be used in network for Power Quality and Energy Management.

ANALYS to Understand

Neptune EMS is your gateway to understanding by Analyzing specific energy consumption for different energy sources organized according to cost centers, products, services or equipments. Set targets to compare them with the results. Analyze the effect of external factors on how energy is used.

SAVE to Get more ... and REPORT it

Neptune EMS empowers you to act with targets on improvements derived from analysis. Continuous monitoring helps to keep control and to follow success immediately at any time, whether it is the result of investment in new equipment, repair, adjustment or maintenance.


The access to archived and real time data on energy purchased lost or sold gives management analysis at the same time, it offers complete connectivity with production and quality management systems in any factory & building.

Unlike most of your overheads, energy is a controllable cost. Energy Management thus becomes an integral part of decision making in your quest for cost control. Energy Management is a process requiring long term management commitment, dedication and right tools. It involves all stake holders from users, technical staff and management.

Neptune EMS brings a wide range of experience in Energy Management to projects for your benefit. Our specialists in software and advance internet applications make sure that Neptune EMS works for you. Our hardware supports a smooth and accurate data transfer. We prefer to work in partnership to create win-win situations. Neptune EMS helps to improve energy and thereby overall company performance with less effort and greater precision. The energy savings will help reduce not only costs, but they add significantly to reducing your carbon footprint.

Benefits

- ▶ Maximising overall energy productivity
- ▶ Increased revenues
- ▶ Accurate picture of energy usage
- ▶ Transparency and track record on all conditions that affect power quality and energy consumption
- ▶ The ability to pay only for what you consume
- ▶ The ability to forecast energy consumption
- ▶ Basis to optimize resource usage
- ▶ Comprehensive insights into energy related performance & cost
- ▶ Relevant information for successful energy efficiency project design
- ▶ Calculation for an excellent rate of return
- ▶ Monitoring & Targeting



Dual Energy Metering Pre-paid & Post-paid with EMS Software & Networking Solution HSN-9028

M302, M306 & M308



- + Micro controller based design
- + CT/PT site selectable
- + Password protection
- + True RMS measurement
- + Auxiliary supply 90–270 VAC/DC
- + Auto ranging, Auto / Manual page scrolling
- + Parameters measured are V, I, Hz, P.F., Kw, Kwh, Kva, HVAR
- + THD-V, THD-I, load hrs.
- + Accuracy Class 1 / 0.5
- + Available with or without RS485
- + Also available in LCD display

Networking with Power Analyzer and Dual Metering for Pre-Paid and Post-paid Solutions



Dual Energy Metering with Automatic meter reading (Pre-paid, Post paid and Hybrid) has become the need of the day. Neptune AMR provide energy usage trends, which helps to control energy consumption and pre-paid and Post-paid billing system, ensuring better recovery on energy usage by calculating the purchased / produced energy, common energy, losses in the energy and total consumption concessionaire wise. It has option for load management, energy management and option to auto disconnect the system due to non payment of dues or over usage of the sectioned load. Comprehensive set of information and reporting system makes it an inevitable tool for sub single / dual source metering.

Power Net = Energy Management System

Power Scan = Energy billing and automated meter reading software

Item Code	L.P. ₹
Kwh Meter M-302	3,200/-
Kwh Meter M-304 with RS-485 Port	On request
Dual Source Kwh Meter M-306 / 5 CTR with RS-485 Port	6,000/-
Dual Source Kwh Meter Direct, up to 60 Amp. M-306D with RS-485 Port	6,800/-
Dual Source Kwh Meter LCD M-308	12,000/-
Power Scan Software- Scanning energy and billing	On request
Power Net Software- Power monitoring and control application	On request

AUTOMATIC METER READING SYSTEM

Automatic Meter HSN-9028



Dual Source Energy Meter
(Single Phase and Three Phase)

Neptune provide host of solution in Dual/Multi source, Pre/Post paid automatic metering systems. Our solutions are designed to automatically collect consumption, Status, Diagnose and transfer the data from the meter to the central for billing, analysis, trouble shouting and historical purpose.

Solution Features


- ▶ Automatic collection of data on specific intervals
- ▶ Integration with web based self-services as users can view consumption, billing etc.
- ▶ Load control, tamper and outage detection.
- ▶ Monitoring of voltage, harmonics and other power quality characteristics.
- ▶ On demand electric meter reading and time of use based meter reading.
- ▶ Remote services for connection & disconnection on non-payment or over demand.
- ▶ Messaging to customers on real time any changes in prices.
- ▶ Automatic detection and reporting of power outages and restoration of services.
- ▶ Automatic messaging alert.
- ▶ Third party integration with SAP and other CRM, PMS software.
- ▶ Integration with window, iOS & Android mobiles.

Software Features

- ▶ Multi layer system which makes it scalable, robust and responsive enough to cater large customer base.
- ▶ Suitably armed software, which has options for Pre-Paid, and both with option of customer information tools like E-mail, SMS, IVR and access to customer on mobile/PDA/Computer.
- ▶ Software supported by well experienced team for support and customization to customer specific requirements.
- ▶ Centrally controlled system with independent local permission & engineering data make the system ideal for multi-site/multi location scenario. Its ready to plug ERP integration module works seamlessly with existing ERP systems.
- ▶ User programmable option to add new heads if any missed at the time of implementation like DG Rates, EB Rates, common Area consumption Rates, facility rates like gym, pool health club, energy tax etc. You think of and head definition is possible.
- ▶ Easy to use system any one can master with minimum training as it has no hassle of printing coupon and then feeding them in the meters, the movement customer pays amount (Cash, Cheque, Card, Net banking) meter is recharged immediately.
- ▶ Transaction based system, where every process is recorded in a very systematic way to enable auditing system.
- ▶ System has in-built basic accounting system to a level that is required at site.
- ▶ System gives option customer to directly view his consumption, load behavior & balance using his unique credential.
- ▶ Solid reporting system built to keep in mind different user like: End Customer, Site Engineers, Site Accounting person, Central Administration Team.

How does Energy Management System work?

System Architecture



Communication Option:

Neptune meters can communicate over various option Like:

1. Wired (Rs485), Ethernet
2. Wirelessly with Power2-Air system, GPRS / GSM bridge
3. Hybrid model of combination of above.

NSL 10 / NSL 10 HD / Ultima

HSN-8532

NSL 10 Capacitors



- + Unique Modular Plastic enclosure
- + Safety, Reliability, long life expectancy, easy handling and mounting
- + A lower dielectric losses means an extended life expectancy of the capacitor
- + The modular design permits a most simple mechanical assembly.
- + Over pressure protection device on each capacitive element
- + Discharge resistors (50v after 1 minute)
- + Self Extinguishing plastic container.
- + Operational Life $\geq 70,000$ hours

NSL – 10 Heavy Duty Capacitors



- + The dielectric consist of heavy film of polypropylene
- + The capacitors are designed with a very low loss dielectric & high quality film is used
- + Operational Life $> 1,00,000$ hours.
- + The safety and reliability of the traditional technology of impregnated used for medium voltage capacitors.
- + Double Protection Safety Device

Ultima – The Ultimate Capacitors



- + Withstands high harmonics overload
- + Life expectancy of more than 2,00,000 hours
- + Low losses ≤ 0.2 W/KVAR
- + Each element is made by Metallized Polypropylene.
- + The Metallization has been made in a special "Profile" to allow: an higher voltage stress on the film.
- + Temp. Range -25 C + 70 C

Item Code	Rating	Price Per KVAR	
		L.P. ₹ 440v	415v / 500v
NSL-10 Capacitor	7.5, 10, 12.5 KVAR & above	335/-	On request
NSL-10 Capacitor	5 KVAR	470/-	On request
NSL-10 HD Capacitor	7.5, 10, 12.5 KVAR & above	395/-	On request
NSL-10 HD Capacitor	5 KVAR	490/-	On request
Ultima Capacitor	10, 12.5 KVAR & above	570/-	On request
Ultima Capacitor	5 KVAR	680/-	On request

Power 9 / Duca Power XD Capacitors HSN-8532

Power 9 Heavy Duty Small Capacitors



- + New compact Heavy Duty Series
- + Cylindrical 3 phase Capacitors
- + Life expectancy >1,00,000 hrs.
- + Low losses ≤ 0.2 w/Kvar
- + Rating available in 1, 2, 3, & 4 Kvar

Power 9 Heavy Duty Capacitors



- + New compact Heavy Duty Series
- + Cylindrical 3 phase Capacitors
- + Life expectancy >1,00,000 hrs.
- + Low losses ≤ 0.2 w/Kvar
- + Rating available in 5, 10, 12.5, 15 & 25 Kvar

Duca Power XD Capacitors



- + Withstand Harmonic Overloads
- + Up to 4 In Max Current
- + Life expectancy >1,70,000 hrs.
- + Low losses ≤ 0.2 w/Kvar
- + Temperature Range - 25 °C to 70 °C

Item Code	Rating	Price Per KVAR	
		L.P. ₹ 440v	525v
Power 9 Capacitor	1, 2, 3, & 4 Kvar	295/-	-
Power 9 Capacitor	5, 10, 12.5 Kvar & above	285/-	-
Ducapower Capacitor XD (Super HD)	10, 12.5, 15, 25 Kvar & above	400/-	On request
Ducapower Capacitor XD (Super HD)	5 Kvar	425/-	On request
LL-M Capacitor	10, 12.5 Kvar & above	610/-	On request
LL-M Capacitor	5 Kvar	720/-	On request
APP Capacitor	-	On request	On request

Automatic Power Factor Controller Single CT HSN-9032

Intelligent P. F. Controller – RM Series



- + LED Type 7 segment 4 Digit Display
- + 8 & 12 capacitors steps available in ON/Off modes
- + Measurement of A, V, PF, Cos phi, W, VAr, VA
- + Automatic calculation of C/k values
- + Program entry for targeted Cos phi value
- + Number of capacitors steps are user definable
- + Automatic / Manual mode selection with indicator light
- + Over voltage, insufficient compensation, overcompensation state alarm indicator lights with output contact

Advance P. F. Controller – Rego



- + The series Rego controller relays are fully static units controlled by an eight bit micro processor with HC mouse technology.
- + Self programming function for power stage and operating logic i.e. no need to set CK setting.
- + Can check health and efficiency of each and individual capacitor bank connected.
- + Measurement of network harmonics, with steps disconnected switch-off when limit value are exceeded.
- + Comprehensive displays with large, three- digit LED display. 3 Logics (1:1), (1:2), (1:2:4) to connect/disconnect banks, with automatic recognition or with standards programs.
- + RS-485 Communication

Item Code	Item Code	L.P. ₹
RM Series		
	RM 6	11,500/-
	RM 8	13,500/-
	RM 12	17,000/-
REGO Series		
	REGO-12	18,000/-

Automatic Power Factor Controller 3 CT HSN-9032

Reactive energy Management 3P – REM series



- + 7 segment LCD display with 2 colors backlite
- + Available in 8 & 12 steps with Rs485 communication port
- + Works on average current
- + Target P.F. 0.8 lag - 0.8 lead, Control sensitivity 55-100%
- + Display THD - I% & THD-V% along with power
- + Measure & Display Voltage & Current
- + Intelligent switching between various capacitor banks
- + Alarm indication by LED & Dual password protection
- + User can configure alarm settings accordingly
- + Fan control can be programmable

Intelligent P. F. Controller – NAAC 3P series



- + LED Type 7 segment 4 Digit Display
- + 8 & 12 capacitors steps available in ON/Off modes
- + Measurement of A, V, PF, Cos phi, W, VAR, VA
- + Automatic calculation of C/k values
- + Program entry for targeted Cos phi value
- + Number of capacitors steps are user definable
- + Automatic / Manual mode selection with indicator light
- + Overvoltage, insufficient compensation, overcompensation state alarm indicator lights with output contact
- + Compensation for all 3 phases

Advance P. F. Controller – G8/ G8 Plus



- + 7 segment LCD Display
- + Suitable for Power Factor Correction using Thyristor Modules for Real Time Compensation & Contractor Switching for normal compensation
- + Master slave function
- + GSM / GPRS Model (optional)
- + Current & Voltage Harmonic analysis
- + Independent compensation for all 3 phases
- + Capacitor over-current protection on all 3 phases

Series	Item Code	L.P. ₹
REM Series		
	REM 3P-8	14,900/-
	REM 3P-12	16,500/-
Neptune 3P Series		
	NAAC 3P-8	18,500/-
	NAAC 3P-12	22,500/-
Intelligent P.F. Series		
	G8 & G8 Plus	On request

Harmonic Block Reactors for Detuned Systems / Thyristor Switching Module

Harmonic Block Reactor HSN-85045090



- + India first single layer design with inbuilt TOP device.
- + 3 Phase aluminium wound reactors with an iron core and air gap
- + Highest quality material and very stringent quality control
- + It has been designed with properties like low temperature rise and lower flux density so that it can operate in worst conditions of ambient and harmonic overloads.
- + Filtering factor of 5.6%, 7% and 14% (any other filtering factor on request)
- + High Linearity ($L > 0.95 \times L_n$): 200%
- + H-Class Insulation
- + Vacuum Impregnated

Rating 440V, 50Hz	Harmonic Block Reactor (AL/Cu) P = 7%	Harmonic Block Reactor 7% with DUCA Power Capacitor (Separate Units)	with Ultima Capacitor
	L.P. ₹	L.P. ₹	L.P. ₹
5 KVAR	7,490/-	9,620/-	10,900/-
10 KVAR	8,990/-	12,990/-	14,700/-
25 KVAR	13,200/-	23,200/-	27,500/-
50 KVAR	22,300/-	42,300/-	50,900/-
100 KVAR	42,500/-	82,500/-	99,500/-

*Copper wound reactor also available on request * Any other Detuned Frequency & rating can be provided on request
NOTE: Prices for 14% & 5.6% Harmonic Block Reactor with and without Capacitor Bank are available on request.

Thyristor switching Module HSN-8541



Electronic switches:

- + Rated Voltage: 415V $\pm 10\%$
- + Temperature controlled, in built forced air cooling in all models

Enclosure: IP 40 Maximum ambient temp: 40 °C Alarms

- + Built-in Alarms for protection of switching module & capacitor Banks

Item Code	Rating (KVAR)	L.P. ₹
Thyristor Switching Module for 415V / 450V application	PS 15 KVAR	26,500/-
	PS 25 KVAR	28,600/-
	PS 50 KVAR	36,000/-
	PS 100 KVAR	63,500/-
Thyristor Switching Module for 690V / 750V application	PS 50 H KVAR	48,600/-
	PS 100 H KVAR	85,000/-
Fast discharge Reactor for 415V / 440V	-	1,400/-
Fast discharge Reactor for 690V / 750V	-	2,250/-

POWERNAC Series P.F. Compensator HSN-8537

Intelligent P.F. Compensator Series-I & II



- + Available from 25 KVAR to 600 KVAR in series-I and series-II
- + Heavy Duty 3 Phase Cylindrical Capacitor
- + Expandable Intelligent PF control for small to medium load network
- + Ultimate solution for compensation of unbalanced loads
- + Measure the reactive power of the system through 3CT's from all 3 Phase
- + Highly intelligent Micro processor based 3 phase P. F. Controller with optional
- + Dual P. F. Setting
- + LCD Controller with inbuilt Load Manager with front optical port
- + Optional Pluggable Data logger, Ethernet, USB RS485, GSM modem and capacitor protection modules
- + Power Coated- Structure finish with attractive Deep Orange and Dark Blue finish
- + Incomer TP-MCCB
- + HRC/MCB's are used for backup protection.

P.F. Compensators are manufactured with standard banking and make P.F. components. Any change in specification will attract different quote.

P.F. Compensator Rating 3Phase, 440v, 50Hz											Unit Price	
Rating KVAR	Banking configuration (kvar)										Wall Mounted	L.P. ₹
25	2	3	5	5	10							97,800/-
30	2	3	5	10	10							99,000/-
40	2	3	5	10	20							1,02,000/-
50	2	3	5	10	10	20						1,10,500/-
60	2	3	5	10	20	20						1,23,000/-
											Type-I Floor Mounted	
75	5	5	15	25	25							1,39,000/-
100	5	5	15	25	25	25						1,52,000/-
125	5	5	15	25	25	25	25					1,68,000/-
											Type-II Floor Mounted	
150	5	5	15	25	25	25	50					2,79,000/-
200	5	5	15	25	25	25	50	50				3,18,000/-
250	12.5	12.5	25	50	50	50	50					3,55,000/-
300	12.5	12.5	25	50	50	50	50	50				3,92,000/-
325	12.5	12.5	25	50	50	50	50	75				4,26,000/-
350	12.5	12.5	25	50	50	50	75	75				4,52,000/-
400	12.5	12.5	25	50	75	75	75	75				5,01,000/-
450	25	50	75	75	75	75	75					5,70,000/-
500	25	50	50	75	75	75	75	75				6,20,000/-
600	25	25	50	50	75	75	75	75	75	75		7,33,000/-

ACTIVCOMP Thyristor Switched / Contactor Switched / Detuned-Tuned Harmonic Filtration Systems HSN-8537

Activcomp System (Real Time thyristor Switched Dynamic Power Factor Correction & Harmonic Filtration System)



- + Fast Real Time Transient-Free switching of Capacitor Bank
- + Prevents damage to sensitive electronic equipment in network
- + Highly intelligent micro processor based 3 phase P.F. Controller with Dual P.F. Setting and Master Slave modes
- + LCD Controller has inbuilt with Load Manager with front optical port
- + Optional pluggable Data Logger, Ethernet, USB, RS485, GSM modem and capacitor protection modules
- + Saves Energy with P.F. Control and Harmonic Filtration
- + Extremely long life expectancy
- + Integral 3 phase Power Quality Analyze showing upto 31st Harmonics
- + Voltage & Current Waveforms
- + Unique Self Testing and Comprehensive reporting and event logging
- + The compensation is based on averaging the FFT analysis of each cycle, resulting in more accurate compensation, even in the presence of harmonics.
- + Available with Tuned, 7%, 5.6%, 14% or any other Tuning frequency as per customer request

Contactor Switching System (Contactor Switched P.F. & Detuned / Tuned Harmonic Filtration System)



- + System is available with Contactor switching for non-dynamic, normal loads-Rating and Dimensions are same as Activcomp System

Activcomp- Thyristor Switched / Contactor Switched Systems are manufactured with standard make of component. Any Change in specification will attract different quote

Output KVAR	Banking Configuration KVAR	Switching Sequence	Dimensions W x D x H (mm)	Thyristor Switched Unit Price	Contactor Switched Unit Price
100	2x12.5, 3x25	1 : 2 : 2	800 x 850 x 2125	On request	On request
200	2x12.5, 1x25, 3x50	1 : 2 : 4	800 x 850 x 2125	On request	On request
300	2x12.5, 1x25, 1x50, 2x100	1 : 2 : 4	800 x 1150 x 2125	On request	On request
400	2x25, 1x50, 3x100	1 : 2 : 4	1600 x 1150 x 2125	On request	On request
500	2x25, 1x50, 4x100	1 : 2 : 4	2400 x 1150 x 2125	On request	On request
600	2x25, 1x50, 5x100	1 : 2 : 4	2400 x 1150 x 2125	On request	On request
700	2x25, 1x50, 6x100	1 : 2 : 4	2400 x 1150 x 2125	On request	On request
800	2x25, 1x50, 7x100	1 : 2 : 4	3200 x 1150 x 2125	On request	On request
900	2x25, 1x50, 8x100	1 : 2 : 4	3200 x 1150 x 2125	On request	On request
1000	2x25, 1x50, 9x100	1 : 2 : 4	3200 x 1150 x 2125	On request	On request

Active Harmonic Filter HSN-8504

Active Harmonic Filter



- + To reduce harmonics of networks with Non-linear loads like UPS, Rectifiers AC & DC drives / VFDs etc. in industrial and commercial installations.
- + Performance meets IEEE and compliance to other international standards.
- + Can be used as Hybrid filter combination of Activcomp with Active filter resulting in reduction of best cost and rating of active filter.
- + Applications- Industries with Harmonic generation loads, Hospitals, Data Centers and IT Facilities, Office Buildings, Airports, Shopping Plazas etc.
- + Improvement in reliability of electrical system leading to lower THD-I & V, reduction in operational problems/cable and transformer losses.
- + Better utilization of distribution Transformer & Generator
- + Increases efficiency, capacitor life, PF, uptime.
- + Easy to commission and use with advance control interface

Hybrid Power Conditioning System



- + Hybrid Power Conditioning System is a combination of Dynamic Activcomp Thyristor based Power factor Correction System and IGBT fired Active harmonic filtration. It offers most viable and economical solution for both Power Factor Compensation and Harmonic Mitigation.

Rating (Amp)	3P 3W Unit Price	3P 4W Unit Price		3P 3W Unit Price	3P 4W Unit Price
Active Harmonic Filter			Hybrid Power Conditioning System		
30 A	On request	On request	300 KVAR + 60 A	On request	On request
60 A	On request	On request	400 KVAR + 100 A	On request	On request
100 A	On request	On request	500 KVAR + 150 A	On request	On request
150 A	On request	On request	600 KVAR + 200 A	On request	On request
200 A	On request	On request	800 KVAR + 300 A	On request	On request
300 A	On request	On request	1000 KVAR + 400 A	On request	On request
400 A	On request	On request			
500 A	On request	On request			
600 A	On request	On request			

Terms & Conditions

Price Basis:

The prices mentioned are Unit Price and Ex-Works basis.
Prices shall be applicable as per our Price List ruling at the time of despatch.

Place of despatch:

The materials shall be despatched from Noida / Delhi works.

GST :

Goods & Service Tax shall be charged extra as applicable at the time of despatch.

Insurance:

Insurance shall be organized, paid, dealt by the customer directly. Damages or any shortages, if found shall be dealt by the customer directly.

Forwarding & Freight Charges:

For all standard items, freight shall be charged extra @3%.
For all other items, e.g. Block Reactors & Panels, freight shall be charged extra at actual.

Terms of Payments:

For all authorized Business Partners, payment terms shall be applicable as per the Trade Policy except APFC Panels & other Panels.
In case of Panels, advance payment & balance along with 100% taxes & duties levies etc. shall be released against PI before despatch.

NOTE: This Price List supersedes all previous Price Lists.

Regional Contacts

Ahmedabad

ahmedabad@neptuneindia.com

Bengaluru

bangalore@neptuneindia.com

Bhopal

bhopal@neptuneindia.com

Chennai

chennai@neptuneindia.com

Chandigarh

Chandigarh@neptuneindia.com

Coimbatore

coimbatore@neptuneindia.com

Haryana

haryana@neptuneindia.com

Hyderabad

hyderabad@neptuneindia.com

Indore

indore@neptuneindia.com

Jaipur

jaipur@neptuneindia.com

Kanpur

kanpur@neptuneindia.com

Kolkata

kolkata@neptuneindia.com

Ludhiana

ludhiana@neptuneindia.com

Mumbai

mumbai@neptuneindia.com

Madurai

madurai@neptuneindia.com

Nagpur

nagpur@neptuneindia.com

Pune

pune@neptuneindia.com

Raipur

raipur@neptuneindia.com

Uttaranchal

uttaranchal@neptuneindia.com

Vadodara

baroda@neptuneindia.com





Corporate & Mktg. Office

A 11 - Sector 59, Noida - 201301, India

Tel: 0120 420 5900, 429 7900

For Product enquiry: +91 955 550 0300

Email: enquiry@neptuneindia.com



www.neptuneindia.com